



APEX MATERIAL INDUSTRIAL VIETNAM COMPANY LIMITED

LÔ A11, KHU CÔNG NGHIỆP KSB-KHU B, XÃ ĐẤT CUỐC, HUYỆN BẮC TÂN UYÊN, TỈNH BÌNH DƯƠNG

Tel: +84-274-3620911/3620777 Fax: +84-274-3620665 Website: <https://www.vnapex.com/>

超微細滑石粉

Ultra-fine Talc Powder

規格	325H	325HA	1250H	2000B	2000A	3000B	3000A
平均粒徑 (µm) Mean particle size	9.0	8.5	6.0	5.0	5.0	4.0	4.0
比表面積 (cm ² /g) Surface area	5500	5500	6500	7500	7500	8500	8500
250目殘餘量 Residue on 250 mesh	≤ 0.3%	≤ 0.3%	≤ 0.1%	≤ 0.05%	≤ 0.05%	≤ 0.05%	≤ 0.05%
疏鬆假比重 (g/cm ³) Loose Bulk density	0.36	0.34	0.25	0.20	0.20	0.16	0.16
白度 Whiteness	92	96	92	92	96	92	96
水分 Moisture	0.2%	0.4%	0.3%	0.4%	0.4%	0.4%	0.4%
燒失量 Loss on ignition	26±6	18±5	26±6	6.5±3	5.5±3	6.5±3	5.5±3
二氧化矽 SiO ₂	54%	63%	54%	62%	63%	62%	63%
氧化鎂 MgO	25%	32%	25%	31%	32%	31%	32%
酸鹼值 pH value	8.5±1	8.5±1	8.5±1	8.5±1	8.5±1	8.5±1	8.5±1

(以上數據為測試平均值供參考。)